



# TS-2 Cut Sheet



## *Features*

- LCD Display, Easy Operation
- Seamless Connectivity with Hydro-X
- Replace Thermostat to Control Commercial AC Units
- No Extra Power Needed
- Micro-SD slot for Firmware Upgrades

## *Overview*

The TS-2 thermostat stations is designed to replace a thermostat connected to a standard HVAC unit. The TS-2 can be used to control most HVAC systems including heat pump and multi-stage HVAC systems. The TS-2 is wired to the HVAC system using the same low-voltage thermostat cable, and has the standard color-coded wiring as most thermostats. The Hydro-x allows separate Day and Night settings for each of up to (4) TS modules, so multiple HVAC systems can be controlled by a single Hydro-X system. The TS-2 also has an adjustable delay time for each HVAC systems being activated. That minimizes high start-up (inrush current) and allows up to 4 HVAC systems to be safely controlled.

# M Product Specifications

## Dimensional Diagram

### Package Content

- 1 x Thermostat Station (TS-2)
- 1 x 16ft RJ12 Cable
- 1 x 4ft RJ12 Cable
- 1 x RJ12 T-Splitter

### Certifications

ETL/FCC

### Degree of Ingress Protection

IP20

### Input Voltage

12V

### Maximum Current

0.1A

### Working Environment

Temperature 32-122°F, Humidity<90%

### Packaging Dimensions

160mm(L) x 86mm(W) x 86mm(H)

### G.W. per pack

0.40kgs

