



# DSD-1 Cut Sheet



## Features

- LCD Display, Easy Operation
- Seamless Connection with Hydro-X
- Multiple purposes assignment
- Plug & Play

## Overview

The Trolmaster DSD-1 Dry-contact module provides a simple and flexible solution to who want to connect & control devices to the Hydro-X using a “dry-contact” or relay to activate the device. Some equipment requires either normally open or normally closed contact closure in order to activate the equipment. The DSD-1 is the product that you need to control those types of devices. \*

The DSD-1 can be configured to work as the other Trolmaster power modules work. The DSD-1 connects into the “devices” line on the Hydro-X and can be set to control an almost infinite number and types of devices such as:

Lighting contactors; Light Deprivation curtains; Pump contactors; Temperature devices; Humidity devices; CO2 devices

\* Consult Trolmaster for questions concerning your particular device.

# **T** Product Specifications

## *Dimensional Diagram*

### **Package Content**

- 1 x Dry Contact Station DSD-1
- 1 x 16ft RJ12 Cable
- 1 x 4ft RJ12 Cable
- 1 x RJ12 T-Splitter

### **Input Voltage**

100~240 VAC, 50/60Hz

### **DC Output**

12V 0.2A

### **Dry Contact Output**

30VDC/250VAC,6A

### **Working Environment**

Temperature 32-122°F, Humidity<90%

### **Packaging Dimensions**

85mm(L) x 80mm(W) x 90mm(H)

### **G.W. per pack**

0.34kgs

